



WOLFKING
DANMARK A/S
DK 4200 Stagelse . Denmark

DATA
MIXER/GRINDER

WALIAN T

BASIC CONSTRUCTION

Stainless steel 18/8 SIS 2333
ASTM 304 Werkstoff 1.4301
Legs Polyamide 6/6

MIXER UNIT

Mixer volume gross 400 litres
Mixer charge max. 200 kgs
Mixing wing speed 26/13 rpm, reversible at 50 cycles
30/15 rpm, reversible at 60 cycles

GRINDER UNIT

Knife and plade dia. 140mm, WOLFKING standard
Grinder worm speed 200 rpm, reversible at 50 cycles
(Waliant) 240 rpm, reversible at 60 cycles
Grinder worm speed 47-284 rpm, reversible at 50 cycles
(Waliant Varispeed) 57-341 rpm, reversible at 60 cycles
Grinder capacity approx. 800 kgs/hour (with 4mm holeplate)

POWER CONSUMPTION

Grinder 7.5 kW
Mixer 2 x 1,6/1,1 kW
Motor norm IEC
Protection class IP 55
Stand-by consumption 20 Watts
Control voltage 24 volts AC
Power connection 25 Amp. earthed 3-phase power plug

Dimensions L x W x H 1600 x 1165 x 1540
Weight Approx. 750 kgs